

SUMGAS Fusion – Clear PVC SPRAY

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Sumgas Fusion - Clear Spray

Product Use: on pvc glue

Supplier Details: Eco Valley Group, LLC.
2600 Douglas Road Suite 501 Coral Gables, FL 33134

Contact: Christian Garaycoa
Phone: 305.992.8758
Email: christian@ecovalleygroup.com
Internet: www.ecovalleygroup.com
Emergency: Chemtrec 800-424-9300

2. HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Gases, 1 Physical,
Flammable Liquids, 2
Physical, Gases Under Pressure, Liquefied Gas Health,
Acute toxicity, 3 Oral
Health, Acute toxicity, 3 Dermal Health,
Acute toxicity, 3 Inhalation
Health, Specific target organ toxicity - Single exposure, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H220 - Extremely flammable gas
H225 - Highly flammable liquid and vapor
H280 - Contains gas under pressure; may explode if heated
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H370 - Causes damage to organs (or state all organs affected, if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

GHS Precautionary Statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. P260 - Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Sumgas Fusion – Clear PVC Spray

P280 - Wear protective gloves/ protective clothing.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P307 +

P311 - IF exposed: Call a POISON CENTER or doctor/ physician.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 -

Eliminate all ignition sources if safe to do so.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients

CAS#	%	Chemical Name
74-98-6		Petroleum gases, liquefied
78-93-3		2-Butanone

4. FIRST AID MEASURES

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

Skin Contact: Irritation may result. Immediately wash with soap and water.

Immediately flush with water, remove any contact lenses, continue flushing with water for at least 15 minutes, then get medical attention.

Ingestion: This product is a gas, refer to the inhalation section.

5. FIRE FIGHTING MEASURES

Flammability: 759°F

Flash Point: 25°F

Flash Point Method: Setaflash closed cup

Lower Explosive Limit: 2.6%

Upper Explosive Limit: 9%

Dry powder, foam, carbon dioxide.

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

6. ACCIDENTAL RELEASE MEASURES

Cleanup:

Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe gas. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas and ventilate closed spaces before entering. Shut off ignition sources: keep flares, smoking or flames out of hazard area.

Small Spills:

Take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills:

Dike far ahead of spill for later disposal.

Sumgas Fusion – Clear PVC Spray

7. HANDLING AND STORAGE

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures. Store away from strong oxidizing agents, chlorine dioxide and/or static discharge.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Alarm detectors should be used when toxic and/or flammable gases may be released. Use process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below recommended exposure limits. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open-air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately and move to fresh air.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: HMIS PP, G | Safety Glasses, Gloves, Vapor Respirator
HMIS PP, C | Safety Glasses, Gloves, Apron Petroleum gases, liquefied
cas#:(74-98-6) []

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested: Vitoject (KCL 890 / Aldrich Z677698, Size M)

Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 60 min Material tested: Camatril (KCL 730 / Aldrich Z677442, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection: impervious clothing, flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a

Sumgas Fusion – Clear PVC Spray

full-face respirator with multi- purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Butanone cas#:(78-93-3) [25-50%] Personal protective equipment

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: Complete suit protecting against chemicals, flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Petroleum gases, liquefied cas#:(74-98-6) [] Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values(TLV) Central Nervous System impairment Cardiac sensitization

TWA 1,000 ppm USA. Occupational Exposure Limits

1,800 mg/m3 (OSHA) - Table Z-1 Limits for AirContaminants The value in mg/m3 is approximate.

TWA 1,000 ppm USA. OSHA - TABLE Z-1 Limits for

1,800 mg/m3 Air Contaminants - 1910.1000

TWA 1,000 ppm USA. NIOSH Recommended 1,800 mg/m3 Exposure Limits

Butanone cas#:(78-93-3) [25-50%]

Sumgas Fusion – Clear PVC Spray

Petroleum gases, liquefied cas#:(74-98-6) [] Components with workplace control parameters
TWA 1,000 ppm USA. ACGIH Threshold Limit Values(TLV) Central Nervous System impairment
Cardiac sensitization

TWA 1,000 ppm USA. Occupational Exposure Limits
1,800 mg/m3 (OSHA) - Table Z-1 Limits for AirContaminants The value in mg/m3 is approximate.

TWA 1,000 ppm USA. OSHA - TABLE Z-1 Limits for
1,800 mg/m3 Air Contaminants - 1910.1000

TWA 1,000 ppm USA. NIOSH Recommended 1,800 mg/m3 Exposure Limits

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Gas	Odor:	Characteristic ketone odor.
Specific Gravity or Density:	0.53		
Boiling Point:	-37.8°C (-36.1°F)	Freezing or Melting Point:	-176.67°C (-286°F)
Vapor Pressure:	586.05 kPa (85 psi) at 21.1°C (70°F)	Autoignition Temperature:	674.44°C (1246°F)
		Upper Flammability Limit and Lower Flammability Limit:	2.5% and 9%

10. STABILITY AND REACTIVITY

Reactivity:	Contains gas under pressure; may explode if headed. Vapor may ignite if exposed to static discharge.
Chemical Stability:	Stable under recommended handling and storage conditions.
Conditions to Avoid:	Direct sunlight. Extremely high or low temperatures. Open flame, heat, sparks, or static discharge.
Materials to Avoid:	Incompatible with strong oxidizing agents, strong caustics, and hydrogen peroxide.
Hazardous Decomposition:	Decomposition may produce carbon monoxide and oxides of carbon.
Hazardous Polymerization:	Carbon oxides.

Sumgas Fusion – Clear PVC Spray

11. TOXICOLOGICAL INFORMATION

Petroleum gases, liquefied cas#:(74-98-6) [] Information on toxicological effects

Acute toxicity: no data available Inhalation: no data available Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available Specific target organ toxicity - repeated exposure: no data available Aspiration hazard: no data available

Additional Information:

RTECS: TX2275000

Dizziness, Drowsiness, Unconsciousness

Butanone cas#:(78-93-3) [25-50%] Information on toxicological effects Acute toxicity:

Oral LD50 no data available Inhalation

LC50 Dermal LD50

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes: no data available Respiratory or skin sensitization: no data

available Germ cell mutagenicity: no data available Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation Toxic if inhaled. May cause respiratory tract irritation. Ingestion Toxic if swallowed. Skin Toxic if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include: Nausea, Dizziness, Gastrointestinal disturbance, Weakness, Confusion., Drowsiness, Unconsciousness, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available Additional

Information: RTECS: Not available

Sumgas Fusion – Clear PVC Spray

12. ECOLOGICAL INFORMATION

Propane see also Petroleum gases, liquefied cas#:(74-98-6) []

Information on ecological effects Toxicity: no data available Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted Other adverse effects: no data available

Butanone cas#:(78-93-3) [25-50%]

Information on ecological effects Toxicity: no data available Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available PBT and vPvB assessment: no data available Other adverse effects: no data available

13. DISPOSAL CONSIDERATIONS

Petroleum gases, liquefied cas#:(74-98-6)

[] Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product. Butanone cas#:(78-93-3) [25-50%] Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal Service to dispose of this material. Contaminated packaging: Dispose of as unused product.

14. TRANSPORT INFORMATION

ID8000, Consumer commodity, 9

15. REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Petroleum gases, liquefied (74-98-6) [n/a%] MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

RQ(5000LBS), 2-Butanone (78-93-3) [n/a%] CERCLA, HAP, HWRORA, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRRA, TSCA,

Sumgas Fusion – Clear PVC Spray

TXAIR, TXHWL

Regulatory CODE Descriptions

RQ = Reportable Quantity

MASS = MA Massachusetts Hazardous Substances List

NJHS = NJ Right-to-Know Hazardous Substances

OSHA WAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean-up substance

HAP = Hazardous Air Pollutants

HWRCRA = RCRA Hazardous Wastes

SARA313 = SARA 313 Title III Toxic Chemicals


TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)

TXHWL = TX Hazardous Waste List

16. OTHER INFORMATION

HMIS III: Health = 1, Fire = 3, Physical

HMIS PPE: Hazard= C - Safety Glasses, Gloves, Apron



Disclaimer: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).